

X2 OCS

A Powerful Intro to a Complete Line of Industrial Control Solutions

Utilising comprehensive, built-in I/O to empower organizations across a multitude of industries.



APPLICATIONS

Agriculture

- Reduce energy consumption
- Increase overall productivity

Building Automation

- Improve occupant comfort
- Economical operation systems

Material Handling

- Minimise HMI inefficiencies
- Track/log/catalogue data

Oil and Gas

- Maximise capacity utilisation
- Maintain emission standards

Renewable Energy

- Data logging, remote access
- Sunlight and UV protection

Water/Wastewater

- Station pump control
- Remote water well controls

MINIMAL PHYSICAL DESIGN

The small, sleek profile of the X2 enables you to fit more in your panel, saving space and resources. For an introductory product, the X2 packs a big picture into an overall small package. With just a 4.6" x 3.5" cutout, the overall design of the X2 is powerful, reliable, and durable.

COMPREHENSIVE I/O CONFIGURATION

In an effort to make implementing Horner OCS controllers as seamless and user-friendly as possible, we have selected a streamlined set of on-board I/O. The wide scope of digital and analogue I/O make automating your applications, and your organisation, as simple as the push of a button. If the built-in I/O of the X2 isn't enough for your specific application, you can easily expand via CAN or serial.

FLEXIBILITY

In the market of fixed I/O, stand-alone controllers, the X2 is unmatched. Suited for most applications across a diverse range of industries, the X2 exceeds standards (and expectations). The intuitive user interface, rugged durability, and suite of capabilities within the X2 are similar to our more established XL line of products.

COMPETITIVE ADVANTAGE

With the addition of the X2 OCS controller, our engineers at Horner Automation have designed a slim, versatile, and complimentary product to our existing line of robust industrial solutions. The X2, when utilised as an introductory piece, empowers your organisation to grow by seamlessly incorporating additional Horner solutions (such as our more advanced X4 or premium X5 OCS controllers) to your expanding system.

SPECIFICATIONS AND TECHNICAL INFORMATION



PHYSICAL CHARACTERISTICS

- 1 Function keys
- 2 USB mini-B port
- 3 High capacity microSD slot
- 4 DC outputs
- 5 DC inputs
- 6 Analogue I/O
- 7 RS232/RS485 serial port
- 8 DC power
- 9 CAN port (via RJ45)

CONTROLLER

CPU	32 Bit Arm
Logic Scan Rate	1.2 mS/K
Built-In Storage	16MB
Removable Memory	32GB microSD
Retentive Storage	32K Battery-Backed Ram
Programming Languages	Advanced Ladder or IEC: ST, LD, FBD, IL, SFC

USER INTERFACE

Display Technology	2.2" Transflective with LED
Resolution / Colour	128 x 64, Monochrome
Keypad	20 Key Domed Membrane

CONNECTIVITY

Serial Ports	1 Port with RS-232 and RS-485
USB Ports (Mini-B)	1 Programming
CAN	1 Port 125K - 1 MB

OPERATING SPECS. & STANDARDS

Primary Power Range	24VDC +/- 10%
Operating Temperature	-10° to 60° C
Humidity	5 to 95% Non-Condensing
Ratings	IP65, UL Type 3R, 4, 4x, 12, 12k, 13

PHYSICAL SPECIFICATIONS

Dimensions	mm: 89.76 tall x 119.18 wide x 35.8 deep in: 3.53 tall x 4.69 wide x 1.41 deep
Weight	270g / 9.5oz

STANDARD ONBOARD I/O

Total Digital Inputs	12 x 24VDC Sinking/Sourcing
Analogue Inputs	4 x 4-20mA
Analogue Outputs	2 x 4-20mA
High Speed Inputs	4 @ 10kHz
High Speed Outputs	2 @ 65kHz

Remote I/O	All Models Support SmartRail, SmartBlock, SmartStix, SmartMod, various 3rd party I/O devices
------------	--

MODEL-DEPENDENT OUTPUTS

HE-X2A	12 x 24VDC Sourcing 0.5A
HE-X2R	6 x Relay 3A, 2 x Sinking 0.5A

ACCESSORIES



SmartRail Modular I/O



SmartStix Terminal Block I/O