

FEATURES

- Off-line probe holders (min flow 20l/h, max flow 80l/h)
- Simple installation
- Bracket for wall mounting
- All cups available transparent or black against sun light

- SAN transparent or black body
- On request it is possible to have one or two additional holes (1/2" or 3/4")



model	electrodes connection	flow sensor	fitting	temperature (°C)	pressure (bar)
■ NPED-E	Eolum	-	6x8	50	5
■ NPED-E2	Etorb2	-	6x8	40	5
■ NPED-E2-EV	Etorb2+valv. mot. 3/4"	-	6x8	40	5
■ NPED-IND	Ecdindpt	-	6x8	40	5
■ NPED-IND PP	Ecdindpt	-	6x8	60	5
■ NPED-INDS	Ecdindspt	-	6x8	40	5
■ NPED1	2 (ø 12-pg13,5)	-	6x8	40	5
■ NPED2	2 (epoxy ø 12)	-	6x8	40	5
■ NPED5	2 (epoxy ø 12) 1 (1/2" thread)	-	6x8	40	5
■ NPED4	2 (epoxy ø 12)	N.c.	6x8	40	5
■ NPED4-1/2	2 (epoxy ø 12) 1 (1/2")	N.o.	6x8	40	5
■ NPED4/2F	2 (epoxy ø 12)	2 wires for N.C. contact instrument	6x8	40	5

ACCESSORIES

description

Cleaning Kit for NPED-E2-EV