

**IDEAL FOR**

- Drinks dispensing
- Beer monitoring
- Cooling equipment
- Semiconductor plant
- Food and beverage

**FEATURES**

- Low cost
- PVDF body
- Sapphire bearings
- Hall effect sensor
- 5 to 24Vdc
- 10 Bar rating
- Viton® seal as standard
- 3/8" John Guest style
- IP65
- 0.1% repeatability
- NSF Certified for use in food and beverage production

**Standard Materials of Construction**

- |               |                |
|---------------|----------------|
| Body and cap  | - PVDF         |
| 'O' Ring seal | - Viton®       |
| Magnets       | - Over-moulded |
| Bearings      | - Sapphire     |

This flowmeter is designed specifically for the drink dispensing industries including beer wines and spirits. They give high performance and competitive pricing with a flow range up to 10 litres per minute. They have totally non-metallic wetted components which makes them the ideal choice for the metering of food based products and even ultra-pure water. The standard inlet tubes are 3/8" push on pipe connectors, for OEM use alternatives are available. The bearings are made of sapphire for long life and reliability, the body is moulded in a choice of thermo-plastics (PVDF as standard) and the 'O' ring seal is typically Viton®.

At the heart of the meter is a precision turbine that rotates freely on robust sapphire bearings and contains over-moulded magnets that are detected through the chamber wall by a Hall effect detector. The output is a stream of NPN pulses that are directly interfaced with the electronic display. This combination of materials and technology ensures a long life product with reliable operation throughout.

**TECHNICAL SPECIFICATIONS**

Model	Flow range L/Min	Linearity % FSD	Typical Freq. Hz.	Approx. 'K' Factor
300-010	0.6 - 10	1.0	235	1420
Weight	0.150kg			

