



The Flowmeter **FLUP** have high visibility on each side and a clear reading of the scale
Thanks to the **conformation of the cone**, at regular increases of flowrate match movements equally regular of the shutter.

Threaded connection head: anodized aluminum

Threads available(F): from 1/4" to 1"1/2 bsp

Body material: Grilamid™ TR55 (PA Transparent) high resistance

O-Ring: NBR; on demand for appropriate quantities available other elastomers

| MODEL | LIQUID | F | FLOWRATE LITRES/MIN | MAX PRESSURE Bar | | A | B | C | Temperature Range: -20 ° C ... +80 ° C | | | | |
|-----------|------------|-----------|---------------------|---------------------|--------------------------------|--|-----|----|--|---|---------|-----|----|
| FLU/P | WATER (H) | 1/4" BSP | 0,1 ... 7 | 30 | Material cone and shutter: PVC | 40 x 40 | 150 | 57 | | | | | |
| | | 3/8" BSP | 0,5 ... 12 | | | | | | | | | | |
| | | 1/2" BSP | 1 ... 20 | | | | | | | | | | |
| | | 3/4" BSP | 5 ... 24 | | | | | | | | | | |
| | | 3/4" BSP | 5 ... 36 | 25 | | 55x 55 | 160 | 72 | | | | | |
| | | 1" BSP | 10 ... 42 | | | | | | | | | | |
| | | 1"1/4 BSP | 20 ... 95 | | | | | | | | | | |
| | | 1"1/2 BSP | 30 ... 120 | | | | | | | | | | |
| | OIL (O) | LIQUID | F | FLOWRATE LITRES/MIN | MAX PRESSURE Bar | Material cone and shutter: Nichel plated brass | A | B | | C | | | |
| | | | 1/4" BSP | 0,1 ... 6 | 30 | | | | | | 40 x 40 | 150 | 57 |
| | | | 3/8" BSP | 0,5 ... 10 | | | | | | | | | |
| | | | 1/2" BSP | 1 ... 16 | | | | | | | | | |
| | | | 3/4" BSP | 5 ... 20 | | | | | | | | | |
| | | | 3/4" BSP | 5 ... 30 | 25 | | | | 55x 55 | | 160 | 72 | |
| 1" BSP | | | 10 ... 35 | | | | | | | | | | |
| 1"1/4 BSP | | | 20 ... 80 | | | | | | | | | | |
| 1"1/2 BSP | 30 ... 100 | | | | | | | | | | | | |

FLU/P 4 C 5-15

| CONNECTION | | | FLOWRATE |
|------------|---------|-----------|----------|
| 1 | WATER | 1/4" BSP | 0,1...7 |
| 2 | WATER | 3/8" BSP | 0,5...12 |
| 3 | WATER | 1/2" BSP | 1...20 |
| 4 | WATER | 3/4" BSP | 5...24 |
| 5 | WATER | 3/4" BSP | 5...36 |
| 6 | WATER | 1" BSP | 10...42 |
| 7 | WATER | 1"1/4 BSP | 20...95 |
| 8 | WATER | 1"1/2 BSP | 30...120 |
| 9 | OIL (O) | 1/4" BSP | 0,1...6 |
| 10 | OIL (O) | 3/8" BSP | 0,5...10 |
| 11 | OIL (O) | 1/2" BSP | 1...16 |
| 12 | OIL (O) | 3/4" BSP | 5...20 |
| 13 | OIL (O) | 3/4" BSP | 5...30 |
| 14 | OIL (O) | 1" BSP | 10...35 |
| 15 | OIL (O) | 1"1/4 BSP | 20...80 |
| 16 | OIL (O) | 1"1/2 BSP | 30...100 |

| FLOWRATE | |
|----------|------------------|
| S | STANDARD |
| C | CUSTOM (MIN-MAX) |