


GENERAL FEATURES

Employment:	Liquid or gas
Accuracy:	±5% del f.s.
Maximun pressure:	10 bar
Maximun Temperature:	70°C
Connections material:	PVC, AISI 304 o AISI 316

OPTIONALS

Proxy switch FP/1 or FP/3 for minumun or maximun flow alarms.

Reinforced version PN 25, PN 40 e PN 64

Opposite fittings special version

Models and Ranges

TIPO	portate standard		attacchi filettati				attacchi flangiati			
	WATER	AIR	threaded connection				flanged connection			
	Lt/h	Nmc/h	DN	A	B	C	DN	A	B	C
R-1	120	6								
	200	8								
	300	10	1/2"	127	35	40	15	127	60	35
	400	12								
	500									
R-2	600		1/2"				15			
	800	15								
	1200		3/4"	160	40	45	20	160	80	40
	1500	25								
	2000		1"				25			
R-3	3000	40	1"	190	40	50	25	190	80	45
R-4	4000									
	6000	60	1"							
	8000		1"1/4	190	40	60	40	190	80	60
	12000	100	1"1/2							

TIPO	SQUARE CONNECTION					
	DN	A	B	C	E	I
R/1	3/8" - 1/2"	127	15	40	40	95
R/2	1/2" - 3/4" - 1"	160	15	45	45	115
R/3	3/4" - 1"	190	15	50	50	125
R/4	1"-1"1/4-1"1/2	238	16	60	40	165

The rates are indicative, it's possible to supply different scale for specific needful

