



**ELECTROMAGNETIC LEVEL INDICATORS WITH ONE CONTACT AND SIDE USE WITH PRESS-FIT CONNECTION**

**USE:**

Made to ensure, with maximum safety, the minimum or maximum level of liquids in tanks compatible with the material of the level indicator.

**OPERATION:**

When the float of the indicator approaches the Reed switch at the pre-established point, the contact activated by the magnet housed in the float opens or closes, thus obtaining the possibility of sending a luminous or acoustic signal or activating or disconnecting any electrical equipment connected to it.

**FITTING:**

The indicator must be fitted in the side position at the required place to be controlled.

**IMPORTANT:**

To invert the contact from N.C. to N.O. just turn the level indicator 180°.

MODEL	MATERIAL	CONNECTION	ELECTRICAL CONTACTS	ELECTRICAL CHARACTERISTICS				CABLE	TEMP. °C	MAX. PRESSURE
				POWER COMMUTABLE IN D.C.	POWER COMMUTABLE IN A.C.	COMMUTABLE VOLTAGE	PROTECTION			
IEG - FCH21 PDA 03	PP	PRESSURE	SPST	50 W	0,5 A	200 VDC 240 VAC	IP 65	30 cm	-20 +80	4
IEG - FCH23 FDA 03	PVDF								-20 +120	2