


ADJUSTABLE ROD LENGTH | STAINLESS STEEL ROD | PVC FOAM FLOAT

**CONNECTION:**

Connector CE  
EN 175301-803-A IP65 PG.9/11



ELECTRICAL CONTACTS	ELECTRICAL CHARACTERISTICS			
	POWER COMMUTABLE IN D.C.	POWER COMMUTABLE IN A.C.	CURRENT STRENGTH IN A.C.	COMMUTABLE VOLTAGE
S1 / S1A / S3 / S3A	60 W	60 V.A.	3 A	230 VDC / VAC
S2	60 W	60 V.A.	1 A	250 VDC / VAC
S1 PLC / S1A PLC	50 W	50 V.A.	1 A	250 VDC / VAC
S2 PLC	20 W	20 V.A.	1 A	150 VDC / VAC

MODEL	PROCESS CONNECTION		ELECTRICAL CONNECTION			RODS		APPLICATION	FLOAT		CALM TUBE		OPERATING TEMPERATURE		ELECTRICAL CONNECTION	
	L	MATERIAL	S	SPST	SPDT	L	MATERIAL		A	B	S	O	I	S	1	2
RL/G1-MAXI	1"	1" GAS	S1	SPST	CLOSED IN THE ABSENCE OF LIQUID	FROM 200 TO 3000	AISI 316 STAINLESS STEEL WITH WELDED BAG HOLDER	S	REED STANDARD	A	CYLINDER Ø70x50	S	NOT PRESENT	-20...+60°C	1	CONNECTOR IP65
	F3	Ø55 WITH 3 HOLES	S1A	SPST	CLOSED IN THE PRESENCE OF LIQUID						FOR L ≤ 1000				2	CONNECTOR IP65 WITH LED
	F2	Ø55 WITH 3 HOLES	S2	SPDT	EXCHANGE					B	OVAL Ø62x100	O	PRESENT IN BRASS		3	ALUMINUM HEAD IP68
	1" 1/4 GAS	1" 1/4 GAS ALUMINUM	S3	SPST	MIN.-EMPTY					C	OVAL Ø85x134	I	PRESENT IN AISI 316 STAINLESS STEEL		4	AISI 316 STAINLESS STEEL HEAD IP68
	1" 1/4 NPT	1" 1/4 NPT ALUMINUM	S3A	SPST	MAX.-EMPTY										FOR L > 1000	L...
RL/G1-MAXI	F3	S2	500	I	S	A	S	S	T							

Maximum working pressure: 10Bar.