



**PNEUMATIC CONTROL LEVEL SWITCH WITH ADJUSTABLE SWITCHING POINT**

**Maximum working pressure: 10Bar.**

- INDICATION BY MEANS OF MAGNETIC-OPERATION PNEUMATIC VALVE
- IP65 ADJUSTABLE PROTECTION BOX WITH INLET AND OUTLET QUICK COUPLINGS
- VALVE OPENING OBTAINABLE IN PRESENCE OR ABSENCE OF LIQUID
- QUICK AND EASY ADJUSTMENT OF SWITCHING POINT, LIKE FOR THE ENTIRE "RL" RANGE

MODEL	PROCESS CONNECTION		PNEUMATIC VALVE		ROD		FLOAT		CALM TUBE		OPERATING TEMPERATURE		BOX		
					L	MATERIAL									
RL/PN	1"	1" GAS ALUMINIUM	S1	PNEUMATIC VALVE OPENING IN THE ABSENCE OF LIQUID - WORK RANGE FROM 2 TO 6 BAR	FROM 90 TO 1000	S	AISI 304 STAINLESS STEEL	S	STANDARD NBR FOR PROCESS CONNECTION 1"	S	NOT PRESENT	S	-15...+60°C	1	ALUMINIUM IP65
	1"1/2	1" 1/2 GAS AISI 316 STAINLESS STEEL	S1A	PNEUMATIC VALVE OPENING IN THE PRESENCE OF LIQUID - WORK RANGE FROM 2 TO 6 BAR		I	AISI 316 STAINLESS STEEL	I	Ø42x83 AISI 316 STAINLESS STEEL WITH STANDARD AISI 316 STAINLESS STEEL STOPS WITH PROCESS CONNECTION 1"1/2	I	PRESENT IN AISI 316 STAINLESS STEEL				
RL/PN	1"		S1		500	S		S		S		S		1	