

Version Code: RL6	PROCESS CONNECTION		Cod.: RL6																				
	THREADED	THREADED	SANITARY FITTING																				
<p>PC polycarbonate loaded</p> <p>DIN B aluminum varnished</p> <p>DIN A Aluminum varnished</p> <p>Special</p>	<p>02 G 1" AISI316 04 1" NPT AISI316 05 G 1" PVC</p>	<p>03 G 1/2" BRASS 04 G 1/2" AISI316 05 1/2" NPT AISI316</p> <p>ONLY WITH SINGOL ELECTRODE AND DIN B HEAD CONNECTION</p>	<p>CLAMP "3A" CONFORM</p> <p>71 DN25 (1") AISI316L 73 DN38 (1 1/2") AISI316L 75 DN51 (2") AISI316L</p> <table border="1"> <tr><th>DN</th><th>A</th><th>E</th></tr> <tr><td>25 (1")</td><td>50.5</td><td>49</td></tr> <tr><td>38 (1 1/2")</td><td>50.5</td><td>49</td></tr> <tr><td>51 (2")</td><td>84</td><td>49</td></tr> </table>	DN	A	E	25 (1")	50.5	49	38 (1 1/2")	50.5	49	51 (2")	84	49								
DN	A	E																					
25 (1")	50.5	49																					
38 (1 1/2")	50.5	49																					
51 (2")	84	49																					
	<p>02 G 1 1/2" AISI316 08 G 1 1/2" PVC 09 G 1 1/2" PTFE</p>	<p>92 G 3/4" AISI 316 93 3/4" NPT AISI316</p> <p>ONLY WITH DIN B HEAD CONNECTION 93/92 ONLY N.1 Ø10 ELECTRODE 94 ONLY N.2 Ø9 ELECTRODE</p>	<p>ACCESSORIES extra -codice</p> <p>SEAL RING PIPE FOR CLAMP WING-NUT</p> <p>DIN 11851</p> <p>20 NW25 AISI304L 21 NW40 AISI304L 22 NW50 AISI304L</p> <table border="1"> <tr><th>NW</th><th>B</th><th>C</th><th>A</th><th>E</th></tr> <tr><td>25</td><td>21</td><td>52-6</td><td>44</td><td>35</td></tr> <tr><td>40</td><td>21</td><td>65-6</td><td>56</td><td>35</td></tr> <tr><td>60</td><td>22</td><td>78-6</td><td>68</td><td>35</td></tr> </table>	NW	B	C	A	E	25	21	52-6	44	35	40	21	65-6	56	35	60	22	78-6	68	35
NW	B	C	A	E																			
25	21	52-6	44	35																			
40	21	65-6	56	35																			
60	22	78-6	68	35																			



RL6 Multi rods electrode
Conductive level control; max 5 rods
Max electrode length: 3m

Housing	
B	Polycarbonate loaded; IP66
E	DIN B aluminum painted (n.1 electrode selection available); IP66
G	DIN A aluminum painted; IP66
Z	Special
Process connection	
02	G 1" / SS316, max 4 electrodes Ø5mm - not for DIN B housing
04	1" NPT-M / SS316 - max 4 electrodes Ø5mm - not for DIN B housing
05	G 1" / PVC - max 4 electrodes Ø5mm - not for DIN B housing
12	G 1" 1/2 / SS316 - not for DIN B housing
18	G 1" 1/2 / PVC - not for DIN B housing
20	DN25 DIN11851 SS304L (sanitary) - only with B housing and 1 electrode
21	DN40 DIN11851 SS304L (sanitary) - only with B housing
22	DN50 DIN11851 SS304L (sanitary) - only with B housing
71	Clamp 1" SS316 - not for DIN B housing
73	Clamp 1" 1/2 SS316 - not for DIN B housing
75	Clamp 2" material SS316 - only for B housing
84	G 1/2" / SS316 - only with DIN B housing and 1 electrode (option B)
85	1/2" NPT-M / SS316 - only with DIN B housing and 1 electrode (option B)
92	G 3/4" / SS316 - only with DIN B housing and 1 electrode Ø10mm (option B)
93	3/4" NPT-M / SS316 - only with DIN B housing and 1 electrode Ø10mm (option B)
99	Special
Nr. of electrodes	
B	1
C	2; only for process fitting cod. 02, 04, 05, 12, 18, 20, 21, 22, 71, 73, 75, 94
D	3; only for process fitting cod. 02, 04, 05, 12, 18, 21, 22, 71, 73, 75
E	4; only for process fitting cod. 02, 04, 05, 12, 18, 21, 22, 71, 73, 75
F	5; only for process fitting cod. 12, 18, 21, 22, 75
Z	Special
Electrodes type, insulation and length - price per 100mm of each electrode (max 3m)	
36	Ø5mm SS316 rod
37	PVC coated Ø5mm SS316 rod
38	PTFE coated Ø5mm SS316 rod
40	Ø10mm SS316 rod, only for one electrode
41	PVC coated Ø10mm SS316 rod, only for one electrode
44	PTFE coated Ø10mm SS316 rod, only for one electrode
99	Special